
MATERIAL SAFETY DATA SHEET

SECTION I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : PAINT THIN/MINERAL SPIRITS 524
 IDENTIFICATION NUMBER : T 19
 PRODUCT USE/CLASS : Solvent

DATE PRINTED: 06/19/02

SUPPLIER:
 The Nelson Paint Co of Michigan Inc
 PO Box 2040
 Kingsford, MI 49802-2040

MANUFACTURER:
 The Nelson Paint Co of Michigan Inc
 PO Box 2040
 Kingsford, MI 49802-2040

EMERGENCY TELEPHONE : 800-255-3924
 CHEMTEL : 24 hours

EMERGENCY TELEPHONE : 800-255-3924
 CHEMTEL : 24 hours

PREPARER: Doyle Yoder, PHONE: 906-774-5566, PREPARE DATE: 05/09/02

SECTION II - COMPOSITION / INFORMATION ON INGREDIENTS

----- CHEMICAL NAME -----	CAS NUMBER	WT. PERCENT		-----OCCUPATIONAL EXPOSURE LIMITS-----				SKIN
		IS LESS THAN	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING		
Aliphatic Hydrocarbons	8052-41-3	100.0 %	100ppm	N.E.	100ppm	N.E.	NO	

(See Section XI for abbreviation legend)

SECTION III - PHYSICAL DATA

BOILING RANGE :	310 - 385 F	VAPOR DENSITY :	Is heavier than air
ODOR :	Solvent	SPECIFIC GRAVITY :	0.7877
APPEARANCE :	Clear Liquid	EVAPORATION RATE :	Is slower than Butyl Acetate
SOLUBILITY IN H2O :	Partial		
VOLATILE BY WEIGHT :	100.0%	VOLATILE BY VOLUME :	100.0%
VOCS, lbs/gal :	6.56	VOCS, grams/ltr :	786

(See Section XI for abbreviation legend)

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT : 100 F	LOWER EXPLOSIVE LIMIT :	1.0 %
	UPPER EXPLOSIVE LIMIT:	6.0 %

EXTINGUISHING MEDIA : CO2 DRY CHEMICAL FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS: Avoid breathing dusts and fumes from burning material. Vapors may form explosive mixture with air. Vapors can travel to a source of ignition and flash back. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Exposure causes skin irritation. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, burning, drying and cracking, skin burns and skin damage. Pre-existing skin disorders may be aggravated by exposure to this material.

Skin absorption is possible, but harmful effects are not expected from this route of exposure under normal conditions of handling and use.

EFFECTS OF OVEREXPOSURE - INHALATION: Short-term inhalation toxicity is low. Breathing small amounts during normal handling is not likely to cause harmful effects; breathing large amounts may be harmful.

Symptoms are more typically seen at air concentrations exceeding the recommended exposure limits. Symptoms of exposure may include: -irritation (nose, throat, respiratory tract) - Pre-existing lung disorders, E.G. asthma-like conditions, may be aggravated by exposure to this material. Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis (characterized by bluish discoloration of the skin and nails) may result from over-exposure to vapor or skin exposure.

EFFECTS OF OVEREXPOSURE - INGESTION: Single dose oral toxicity is low. Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing large amounts may be harmful.

Symptoms may include:

-Mouth and throat irritation

-Gastrointestinal irritation (nausea, vomiting, diarrhea).

-Central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Based on the available information, this material cannot be classified with regard to carcinogenicity.

This material is not listed as a carcinogen by IARC, NTP or OSHA.

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for 15 minutes. Get immediate medical attention.

FIRST AID - SKIN CONTACT: Immediately flush skin with plenty of water. Wash with soap and water. Remove soiled clothing. Wash clothing separately before reuse. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: Keep person warm, quiet and get immediate medical attention. Do NOT induce vomiting, because aspiration of material into the lungs from vomiting can cause chemical pneumonitis which can be fatal.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT INHALATION

SECTION VI - REACTIVITY DATA

HAZARDOUS DECOMPOSITION PRODUCTS: May form:, Carbon Dioxide and Carbon Monoxide, etc.

CONDITIONS TO AVOID: Heat, sparks and open flames.

INCOMPATIBILITY: Avoid contact with: strong oxidizing agents.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Evacuate all non-essential personnel. Remove all sources of ignition. Ventilate the area. Equip employees with appropriate protection equipment. Dike around spilled material. Cover spill with absorbent material and shovel with non-sparking tools into container. Remove containers to safe area and seal. Avoid runoff into storm sewers and ditches which lead to waterways.

WASTE DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

VENTILATION: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves, a chemical suit and rubber boots.

EYE PROTECTION: Do not wear contact lenses. Wear safety glasses with side shields or goggles.

OTHER PROTECTIVE EQUIPMENT: Where splashing is possible, full chemically resistant protective clothing and boots are required.

HYGENIC PRACTICES: Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor Liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Wash hands before eating or smoking. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep away from heat, sparks and flame. Keep container closed when not in use.

OTHER PRECAUTIONS: Warning!!! Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions. Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a sufficiently high level, sparks can form that may ignite the vapors of flammable liquids.

SECTION X - HMIS RATINGS

HMIS RATINGS - HEALTH: 1 FLAMMABILITY: 2 REACTIVITY: 0

SECTION XI - OTHER REGULATIONS

SARA SECTION 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT % IS LESS THAN
No SARA Section 313 components exist in this product.		

PREVIOUS MSDS REVISION DATE: 05/04/98

LEGEND : N.A. - Not Applicable, N.E. - Not Established
N.D. - Not Determined

***** DISCLAIMER *****

The Nelson Paint Company, Inc. (TNPC) expressly disclaims all expressed or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein. All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, TNPC makes no representations as to its accuracy or sufficiency. Conditions of use are beyond TNPC's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

(END OF MSDS)